GT-3303		
Model	GT-3303	
Item	Wireless Portable 2D Barcode Scanner	
Physical Parameter		
Material	ABS + PC	
Power Supply	Charge DC 5V ±5% ； 3.7V 1000mA lithium battery	
Operating Current	0.41W（Working）; 0.20W（Standby）; 0.75W（Peak）	
Weight	77g±3g（without cable）	
Size	L * W * H: 119.5 *43.5 * 25.5（unit/mm）	
Color	White	
Button Lifespan	＞100000 times	
Performance Parameter		
Interface	USB; 2.4G; Bluetooth	
System Supported	Linux, Android, Windows XP、7、8、10, MAC	
Language Supported	English-United States; French-Canada; Dutch-Netherlands; Spanish-International; Latin American-Argentina; Portuguese-Brazil; Danish-Denmark; Italian-Italy 142; French-France; German-Germany; Portuguese-Portugal; Finnish-Finland; Turkish-F; Japanese; Russian-Russia; Northern Sami-Norway 【Support multi-country keyboard】	
Sensor	838×640 Global exposure CMOS	
Processor	32-bit ARM MCU + BGA	
storage	512 KB（Capacity can be customized）	
Light Source	White LED illumination + RED LED Positioning	
Motion Tolerance	Code128： 35cm/sec QR： 45cm/sec	
Wireless transmission distance	2.4G≤50-70m（Visual range） Bluetooth≤30m（Visual range）	
Reading Mode	Image	
Resolution	≥5mil	
Bit Error Rate	1/500万	
Button Functions	1, Side Button(Double click to enter storage mode+Long press for 8s to shutdown） 2, Home Button（Click to enter scanning mode+Long press for 10s to enter Bluetooth mode）	
Trigger Mode	Manual ; Continuous scanning;Auto-sensing	
Prompt Mode	Buzzer, Indicator Light,Vibration	
Scanning Angel	tilt±60°, deflection±60°, Spin 360°	
Print Contrast	≥25%	
Charging time	appr.3.5h	
Working time	appr.9h	
Decoding Capability — 1D	◎Interleaved 2 of 5 ◎ITF-6 ◎ITF-14 ◎ISBN ◎Code 11 ◎UCC/EAN-128 ◎GS1 Databar ◎Matrix 2 of 5 ◎Industrial 2 of 5 ◎Code 128 ◎EAN-13 ◎EAN-8 ◎Code 39 ◎UPC-A ◎UPC-E ◎Codabar ◎MSI-Plessey ◎Code 93	
Decoding Capability — 2D	◎PDF417 ◎Data Matrix ◎QR Code ◎AZTEC ◎Micro QR ◎Micro PDF417	
Scanning Depth	Code39 5mil：5cm - 12cm QR 15mil：3cm - 25cm	
Environment Parameter		
IP Grade	IP42	
Operating Temp.	0 to 50℃ / 32 to 122℉	
Storage Temp.	0 to 50℃ / 32 to 122℉	
Operating Humidity	20% to 85%（No Condensation）	
Storage Humidity	20% to 85%（No Condensation）	
ESD Protection	15KV air discharge	
Shock Resistance	1.2m free fall on concrete surface	
Ambient light	0→100000Lux	
International Certification		